

Thermal Transfer Ribbons for

- **Heatshrink and TIPTAGs**

The thermal transfer print technology is based on heating up certain dots in the print head. This transfers the ink very precisely from the ribbon onto the surface of the printed material.


Features and Benefits

- Thermal transfer ribbons for highest quality and performance of printed markers
- Ribbons are specifically designed to maximise print performance for the recommended material



Ribbons for printing on Tubing and TIPTAGs.

ID: The standard inside core diameter is 25.4 mm.



TYPE	Recommended Material	Colour	Width (W)	Length (L)	Article-No.
TTRC+ 30MM	TIPTAG/TIPTAG PU/TULT/TCGT/TLFX	Black (BK)	30.0	300.0 m	556-00114
TTRC+ 60MM	TIPTAG/TIPTAG PU/TULT/TCGT/TLFX	Black (BK)	60.0	300.0 m	556-00115
TTRC+ 100MM	TIPTAG/TIPTAG PU/TULT/TCGT/TLFX	Black (BK)	100.0	300.0 m	556-00103
TTDTHOUT 40MM	TIPTAG/TULT/TCGT/TLFX/TULT DS/ TLFX DS	Black (BK)	40.0	300.0 m	556-00139
TTDTHOUT 60MM	TIPTAG/TULT/TCGT/TLFX/TULT DS/ TLFX DS	Black (BK)	60.0	300.0 m	556-00140
TTDTHOUT 100MM	TIPTAG/TULT/TCGT/TLFX/TULT DS/ TLFX DS	Black (BK)	100.0	300.0 m	556-00141
TT822OUT8 110MM	TULT/TCGT	Silver Grey (SRGY)	110.0	300.0 m	556-00161
TTRW 30MM	TULT/TCGT	White (WH)	30.0	300.0 m	556-00125
TTRW 60MM	TULT/TCGT	White (WH)	60.0	300.0 m	556-00137
TTRW 100MM	TULT/TCGT	White (WH)	100.0	300.0 m	556-00133

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

RoHS