

# HRC blade type cartridge fuses

## gG/aM type



Dimensions (p. 95)

Pack	Cat. Nos.	Type gG (IEC)/gL (VDE)		
		HRC (high rupturing capacity) Conform to BS EN 60269-1 and 2, IEC 60269-1,2 and 2-1, VDE 0636-21 Bureau Veritas approved Fully insulated end plate and handle lugs		
	With indicator	Rating (Amps)	Voltage ~ (Volts)	Breaking capacity (Amps)
	<b>Size 00</b>			
10	0163 18	25	500	120 000
10	0163 20	32		
10	0163 25	40		
10	0163 30	50		
10	0163 35	63		
10	0163 40	80		
10	0163 45	100		
10	0163 50	125		
10	0163 55	160		
	<b>Size 0</b>			
3	0168 45	100	500	120 000
3	0168 50	125		
3	0168 55	160		
3	0168 60 <sup>(1)</sup>	200		
	<b>Size 1</b>			
3	0173 50	125	500	120 000
3	0173 55	160		
3	0173 60	200		
3	0173 65	250		
	<b>Size 2</b>			
3	0178 60	200	500	120 000
3	0178 65	250		
3	0178 70	315		
3	0178 75	400		

Pack	Cat. Nos.	Type aM (motor rated)		
		HRC (high rupturing capacity) Conform to BS EN 60269-1 and 2, IEC 60269-1,2 and 2-1, VDE 0636-21 Bureau Veritas approved Fully insulated end plate and handle lugs		
	With indicator	Rating (Amps)	Voltage ~ (Volts)	Breaking capacity (Amps)
	<b>Size 00</b>			
3	0160 25	40		
3	0160 30	50		
3	0160 35	63		
3	0160 40	80		
3	0160 45	100	400	
3	0160 50	125		
	<b>Size 0</b>			
3	0165 35	63		
3	0165 40	80		
3	0165 45	100	500	120 000
3	0165 50	125		
3	0165 55	160		
	<b>Size 1</b>			
3	0170 50	125	500	120 000
3	0170 55	160		
3	0170 60	200		
3	0170 65	250		
	<b>Size 2</b>			
3	0175 60	200	500	120 000
3	0175 65	250		
3	0175 70	315		

Neutral blades		
1	0168 04	Size 0
1	0173 04	Size 1
1	0178 04	Size 2
1	0181 04	Size 3

(1) Overrating not described by standards