

Marina wall mounting enclosures

polyester (GRP) IP 66 - IK 10



0362 56



0362 76



0362 63 + plinth Cat. No. 0362 92
+ roof Cat. No. 0362 95



0362 55 +
wall brackets Cat. No. 0364 09




0362 56
on stand Cat. No. 0364 36
and crosspieces
Cat. No. 0364 39

Technical information and dimensions (p. 19-20)
Equipment (p. 23-32)

Grey RAL 7035
IP 66 according to IEC EN 60529
IK 10 according to IEC EN 62262 (EN 50102)
Class II insulation for final assembly according to IEC EN 60439-1
Glass fibre reinforced polyester (GRP) enclosures
Self extinguishing at 960 °C according to IEC EN 60695-2-11
Designed for corrosive environments
Reversible door, 180° opening⁽¹⁾
2 x double bar locks⁽¹⁾
Captive stainless steel hinge pins⁽¹⁾
Mounting plate/equipment can be fixed directly to the rear of the enclosure
Accepts partial plate from 500 x 400 x 200 mm and/or rails⁽¹⁾
Optional depth adjustment kit (Cat. No. 0362 42) available for enclosures 400 mm high and above
For wall mounting, wall mounting brackets must be ordered separately

Pack	Cat. Nos.	GRP enclosures					
Plain door							
External dimensions (mm)							
		Height	Width	Depth	Weight (kg)		
1	0362 50	300	220	160	1.75		
1	0362 51	400	300	206	3.7		
1	0362 52	500	400	206	5.1		
1	0362 55	610	400	257	6.4		
1	0362 56	720	510	250	11.2		
1	0362 61	820	610	300	15.2		
1	0362 63	1020	810	300	21.8		
1	0362 64	1220	810	300	25.0		
Glazed door with tinted glass window							
External dimensions (mm)							
		Height	Width	Depth	Window (mm)	Weight (kg)	
					Height	Width	
1	0362 71	400	300	206	235	145	4.0
1	0362 72	500	400	206	335	245	5.6
1	0362 75	610	400	257	463	245	7.0
1	0362 76	720	510	250	570	272	12.3
1	0362 81	820	610	300	672	372	16.7



Pack	Cat. Nos.	Roofs	
IK 10			
For enclosures (mm)			
		Width	Depth
1	0362 93	500	250
1	0362 94	600	300
1	0362 95	800	300

Pack	Cat. Nos.	Plinths	
Height 170 mm Front and rear trap door Possibility to overlap 2 plinths			
For enclosures (mm)			
		Width	Depth
1	0362 91	600	300
1	0362 92	800	300

Pack	Cat. Nos.	Fixing accessories	
IP 66 maintained			
Wall mounting brackets Set of 4, supplied with screws			
For enclosures			
		Height (mm)	Max. load (kg)
1	0364 08	300	100
1	0364 09	400 to 1 200	150
Rear with threaded rod M8 for enclosures height ≥ 400 mm Mounting at back of enclosures			
10	0362 40		
On ground Stand comprised of 2 feet for fixing enclosures high up Supplied with fixing screws Hot galvanised steel Conform to EN 50125-3 (railway applications, fixed installations)			
For enclosures			
		Height (mm)	
1	0364 36	400 to 800	
1	0364 37	1 000 to 1 200	
1	0364 39	Anti-tipping crosspieces	

Pack	Cat. Nos.	Accessories	
1	0362 42	Depth adjustment kit for enclosures ≥ 200 mm 4 fixings complete with screws	



Plain and perforated plates (see p. 23)

Modular chassis (see p. 25)

Internal doors (see p. 25)

Sectioned uprights (see p. 26)

Crosspieces (see p. 26)

Locking accessories (see p. 28)

(1) Except Cat. No. 0362 50