

Atlantic-E steel wall mounting enclosures

IP 66 - IK 10

NEW



0399 30



0399 35



0399 43




0365 53

Technical information and dimensions (p. 15)
Equipment (p. 23-32)

Pack	Cat. Nos.	Steel enclosures			
		Grey RAL 7035 IP 66 according to IEC 60529 IK 10 according to IEC 62262, EN 50102 Supplied with : galvanised plain mounting plate (removable), earth connection braid and wall mounting brackets Reversible door Supplied with one double bar lock up to 500 x 500 x 250 mm and 2 double bar locks from 600 x 400 x 150 mm Removable cable entries plate Can be equipped with Cabstop plates Can be equipped with Lina 12.5 and Lina 25 perforated plates, sectioned uprights, DIN rail or chassis with insulating faceplates (p. 23-26) 80 µ thick textured polyester coating			
		Dimensions (mm)			
		Height	Width	Depth	Weight (kg)
1	0399 30	300	200	150	4.5
1	0399 31	300	300	150	4.7
1	0399 32	300	300	200	4.8
1	0399 33	300	400	200	6.7
1	0399 34	400	300	150	6.25
1	0399 35	400	300	200	6.7
1	0399 36	400	400	200	10.5
1	0399 37	400	600	250	13.5
1	0399 38	500	400	150	11
1	0399 39	500	400	200	11.5
1	0399 40	500	400	250	12
1	0399 41	500	500	250	12.5
1	0399 42	600	400	200	13
1	0399 43	600	400	250	13.5
1	0399 44	600	500	200	16
1	0399 45	600	500	250	16.5
1	0399 46	600	600	250	17
1	0399 51	700	500	200	20
1	0399 52	700	500	250	21
1	0399 54	800	600	200	27
1	0399 55	800	600	250	30
1	0399 56	800	600	300	31.7
1	0399 59	800	800	300	33.5
1	0399 63	1000	600	300	48
1	0399 64	1000	800	250	49.5
1	0399 65	1000	800	300	52
1	0399 69	1200	800	300	62

		Roofs		
		Grey RAL 7035 Steel Possible adjustment ±20 mm (front or back)		
		For enclosures		
		Width (mm)	Depth (mm)	Weight (kg)
1	0365 51	300	200	1.2
1	0365 52	400	200	1.4
1	0365 53	400	250	1.8
1	0365 64	500	250	2
1	0365 54	600	250	2.5
1	0365 56	600	300	3
1	0365 57	800	300	3.6

Pack	Cat. Nos.	Plinths			
		Anthracite grey RAL 7021 Height 200 mm Front and rear trap door For 300 mm deep enclosures			
		Enclosure width (mm)		Weight (kg)	
1	0363 00	600		6	
1	0363 01	800		6.7	
		Cabstop plates IP 55			
		Open-work plates			
		Grey RAL 7035 Cable entries consisting of a cable clamp providing the mechanical grip, and elastomer areas for weatherproofing Can be pierced using the cable (no tool required) Fits the cable perfectly Replacement of a cable possible Fire retardant polypropylene Supplied with : - locking caps for sealing a pierced entry providing IP 55 protection - cable release tool			
		Number of entries ø5 to 14 (mm)	Number of entries ø14 to 24 (mm)	Number of spare entries	Direct mounting on cable entry of Atlantic-E enclosure width (mm)
1	0364 95	13	1	1	400
1	0364 97	28	2	2	600-800-1200
		Wall mounting brackets			
		Grey RAL 7035 For heavy loads up to 300 kg Horizontal or vertical installation With a roof, horizontal installation only Zamak Supplied with cover			
1	0364 01	Set of 4			
		Locking accessories			
		Metal rebate lock barrels			
10	0399 80	6 mm female square			
10	0399 81	8 mm male triangle			
		Keys for rebate locks			
10	0365 35	6 mm female square			
10	0365 40	8 mm male triangle			
		Key barrels			
		Supplied with set of 2 keys			
		For key No :			
10	0399 86	405			
10	0399 87	455			
10	0399 88	2433 A			
10	0365 45	Set of two 2433 A keys			



For Lina 12.5 and Lina 25 perforated plates see p. 23
For modular chassis see p. 25
For sectioned uprights see p. 26
For crosspieces see p. 26