

Hypra® IP 66/67-55 - LV 32 A

plastic plugs and sockets



0530 50 + 0529 40

Technical information and dimensions (p. 183-185)
Conformity to International Standards (p. 204)

Conform to BS EN 60309-1, BS 60309-2, IEC 60309-1 and IEC 60309-2
 IP according to BS EN 60529 and IEC 60529

IK 09
 Self-extinguishing : 850 °C for insulated parts, 650 °C for housing
 Stainless steel external screws - Nickel plated brass contacts
 Temp. rating : -50 °C to +100 °C

Pack Cat. Nos. Straight plugs 32 A

Pack	Cat. Nos.	Configuration	Voltage
1	0530 56	2 P + \perp	100 to 130 V~
1	0530 60	3 P + \perp	380 to 415 V~
1	0530 61	3 P + N + \perp	380 to 415 V~

Pack Cat. Nos. Angled plugs 32 A

Pack	Cat. Nos.	Configuration	Voltage
1	0530 06	2 P + \perp	100 to 130 V~
1	0530 10	3 P + \perp	380 to 415 V~
1	0530 11	3 P + N + \perp	380 to 415 V~

Pack Cat. Nos. Mobile sockets 32 A

Pack	Cat. Nos.	Configuration	Voltage
1	0530 76	2 P + \perp	100 to 130 V~
1	0530 80	3 P + \perp	380 to 415 V~
1	0530 81	3 P + N + \perp	380 to 415 V~

Pack Cat. Nos. Panel mounting sockets (modular) 32 A


Pack	Cat. Nos.	Configuration	Voltage
1	Modular 0530 46	2 P + \perp	100 to 130 V~
1	0530 50	3 P + \perp	380 to 415 V~
1	0530 51	3 P + N + \perp	380 to 415 V~

Back boxes

Pack	Cat. Nos.	Description
1	0529 40	Surface mounting boxes For LV 32 A 2 P + \perp / 3 P + \perp / 3 P + N + \perp sockets
5	0529 90	Through entry surface mounting boxes For LV 32 A 2 P + \perp / 3 P + \perp / 3 P + N + \perp sockets

Hypra® IP 66/67-55 - LV 63 and 125 A

plastic plugs and sockets



0595 32



0594 27

Technical information and dimensions (p. 183-185)

Conform to BS EN 60309-1, BS 60309-2, IEC 60309-1 and IEC 60309-2
 IP according to BS EN 60529 and IEC 60529

IK 09
 Self-extinguishing : 850 °C for insulated parts, 650 °C for housing
 Stainless steel external screws - Nickel plated brass contacts
 Temp. rating : -50 °C to +100 °C
 LV 63 A and 125 A have a pilot pin

Pack Cat. Nos. Straight plugs 63 and 125 A

Pack	Cat. Nos.		Configuration	Voltage
1	63 A 0594 47	125 A 0595 22	3 P + \perp	380 to 415 V~
1	0594 48	0595 23	3 P + N + \perp	380 to 415 V~

Pack Cat. Nos. Mobile sockets 63 and 125 A

Pack	Cat. Nos.		Configuration	Voltage
1	63 A 0594 87	125 A 0595 32	3 P + \perp	380 to 415 V~
1	0594 88	0595 33	3 P + N + \perp	380 to 415 V~

Pack Cat. Nos. Surface mounting sockets 63 and 125 A

Pack	Cat. Nos.		Configuration	Voltage
1	63 A 0594 37	125 A 0595 02	3 P + \perp	380 to 415 V~
1	0594 38	0595 03	3 P + N + \perp	380 to 415 V~

Pack Cat. Nos. Panel mounting sockets 63 and 125 A

Pack	Cat. Nos.		Configuration	Voltage
1	63 A 0594 27	125 A 0595 12	3 P + \perp	380 to 415 V~
1	0594 28	0595 13	3 P + N + \perp	380 to 415 V~