

Synergy® metalclad

switches and socket outlets



Finish : grey epoxy coated steel
Terminal screws captive and backed off ready for cabling
Supplied complete with close fit surface mounting back box with knockouts

| Pack | Cat. Nos. | Single pole plate switches 10 AX - 250 V~ |
|------|-----------|---|
| | | Conform to BS EN 60669-1 : 2000 Nominal dimensions : 86 x 86 x 43 mm |
| 5 | 7338 00 | 1 gang – 1 way |
| 5 | 7338 01 | |
| 5 | 7338 05 | |
| 5 | 7338 02 | 2 gang – 2 way |
| 5 | 7338 03 | 3 gang – 2 way |

| Pack | Cat. Nos. | Double pole socket outlets 13 A - 250 V~ |
|------|-----------|---|
| | | Conform to BS 1363 - Part 2 : 1995 2 earth terminals Nominal dimensions : 86 x 86 x 43 mm |
| 5 | 7338 60 | 1 gang – switched |
| 5 | 7338 61 | 1 gang – switched + red LED power indicator |
| | | Nominal dimensions : 86 x 146 x 43 mm |
| 5 | 7338 70 | 2 gang – switched |
| 5 | 7338 71 | 2 gang – switched + red LED power indicator |

| Pack | Cat. Nos. | Unswitched and key switched socket outlets 13 A - 250 V~ |
|------|-----------|---|
| | | Conform to BS 1363 - Part 2 : 1995 2 earth terminals Nominal plate dimensions : 1 gang - 86 x 86 mm 2 gang - 86 x 146 mm |
| 10 | 7338 65 | 1 gang – unswitched |
| 5 | 7338 75 | 2 gang – unswitched |
| 1 | 8200 73 | 2 gang single socket with DP key switch |

| Pack | Cat. Nos. | RCD sockets 13 A - 250 V~ |
|------|-----------|---|
| | | Conform to BS 7288 : 1990 and BS 1363 - Part 2 : 1995 Conventional earth pin release shutter Maximum operating current 16 A Incorporate a “test and reset” button Nominal dimensions : 86 x 146 x 43 mm |
| | | Active (electronically latched) - trips in the event of a power failure - suitable in applications where automatic restoration of supply would be hazardous, e.g. machinery, power tools |
| 1 | 7338 97 | RCD unit 2 gang DP 30 mA active |
| | | Passive (mechanically latched) - does not trip in the event of a power failure - suitable in applications where automatic restoration of supply is required, e.g. fridge, freezer, unmanned areas |
| 1 | 7338 98 | RCD unit 2 gang DP 30 mA passive |

| Pack | Cat. Nos. | Socket outlets 15 A - 250 V~ |
|------|-----------|--|
| | | Conform to BS 546 : 1950 Nominal dimensions : 86 x 86 x 43 mm |
| 5 | 7338 88 | 1 gang – unswitched |
| 5 | 7338 89 | 1 gang – switched |