

Tenby® Rapid Clamp Ultra earth clamps



0343 85



0343 86



0343 87

Conform to BS 951 : 2009

Available in three sizes

Suitable for dry, non corrosive atmospheres and corrosive or humid conditions

Resistance of incandescent wire 960 °C

Resistivity of 0.4 mΩ

Colour : grey

Polyamide

Safe, intuitive 1/4 turn mounting ensuring an excellent, lasting equipotential link

Pack	Cat. Nos.	Earth clamps for all conditions			
		Pipe Ø		Connection cross-section	
		Ø min. (mm)	Ø max. (mm)	min. (mm ²)	max. (mm ²)
20	0343 85	12	16	2.5	16
10	0343 86	18	22	2.5	16
10	0343 87	28	32	2.5	16

Tenby® Rapid Clamp earth clamps



EC14



EC15/2



EC16/3

Conform to BS 951 : 2009

Available in three types :

Red (EC14) for dry, non corrosive atmospheres

Blue (EC15) for corrosive or humid conditions

Green (EC16) for corrosive or humid conditions, large earth conductors

5 standard band lengths to suit pipe Ø of 12-32 mm, 32-50 mm, 50-75 mm, up to 100 mm and up to 150 mm

Pack	Cat. Nos.	Earth clamps for dry conditions
		Terminal size : A – D (2.5 – 10 mm ²) Maximum earth conductor 1 x 10 mm ²
20	EC14	For pipe Ø 12 – 32 mm
20	EC14/2	For pipe Ø 32 – 50 mm
20	EC14/3	For pipe Ø 50 – 75 mm

Pack	Cat. Nos.	Earth clamps for all conditions
		Terminal size : A – D (2.5 – 10 mm ²) Maximum earth conductor 1 x 10 mm ²
20	EC15	For pipe Ø 12 – 32 mm
20	EC15/2	For pipe Ø 32 – 50 mm
20	EC15/3	For pipe Ø 50 – 75 mm
20	EC15/4	For pipe Ø up to 100 mm
20	EC15/6	For pipe Ø up to 150 mm
		Terminal size : A – E (2.5 – 16 mm ²) Maximum earth conductor 2 x 16 mm ²
20	EC16	For pipe Ø 12 – 32 mm
20	EC16/2	For pipe Ø 32 – 50 mm
20	EC16/3	For pipe Ø 50 – 75 mm