

Technical data sheet - Metal fitting with shield termination TOP-T-S-EMV1

Cable fittings and accessories



Identification	Type	TOP-T-S-EMV1 M 16x1,5
	Part-No.	600171
Use/Area of application		
Properties	<ul style="list-style-type: none">• Cable fitting with hexagon base• Strain relief• Gasket• O-Ring and EMC compliant shield termination• Simple installation - the shield braiding with plastic insert is pressed against fitting base	
Technical data		
Strain relief	Yes	
Material	Brass nickel-plated	
Protection class	IP 68 to 5 bar	
Anti-kink device	without anti-kink device	
Gasket	Neoprene	
O-Ring (OR)	Perbunan®	
Clamping range D	5.5 – 10.0 mm	
weight approx.	1.67 kg/100 piece	
Thread	M 16	
Design		
G	M 16x1.5	

08.12.2012 – Subject to technical modification

Part-No. 600171

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


Technical data sheet - Metal fitting with shield termination TOP-T-S-EMV1

L 1	5.5 mm
SW	17 mm

General

PU	100 piece
Note	Simple installation - the shield braiding with plastic insert is pressed against fitting base.

Dimensions



d 8.2 mm

08.12.2012 – Subject to technical modification

Part-No. 600171

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY