

# Technical data sheet - Metal fitting with shield termination TOP-T-S-EMV1

Cable fittings and accessories



<b>Identification</b>	Type	TOP-T-S-EMV1 M 20x1,5
	Part-No.	600172
<b>Use/Area of application</b>		
Properties	<ul style="list-style-type: none"><li>• Cable fitting with hexagon base</li><li>• Strain relief</li><li>• Gasket</li><li>• O-Ring and EMC compliant shield termination</li><li>• Simple installation - the shield braiding with plastic insert is pressed against fitting base</li></ul>	
<b>Technical data</b>		
Strain relief	Yes	
Material	Brass nickel-plated	
Protection class	IP 68 to 5 bar	
Anti-kink device	without anti-kink device	
Gasket	Neoprene	
O-Ring (OR)	Perbunan®	
Clamping range D	8.0 – 13.0 mm	
weight approx.	2.88 kg/100 piece	
Thread	M 20	
<b>Design</b>		
G	M 20x1.5	

08.12.2012 – Subject to technical modification

Part-No. 600172

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY


# Technical data sheet - Metal fitting with shield termination TOP-T-S-EMV1

L 1	6.0 mm
SW	22 mm

## General

PU	100 piece
Note	Simple installation - the shield braiding with plastic insert is pressed against fitting base.

## Dimensions



d	11.5 mm
---	---------

## Certification



08.12.2012 – Subject to technical modification

Part-No. 600172

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY