

Technical data sheet - Cablefix Vario

Feed-through for all prefabricated cables and wires with connectors



Cable fittings and accessories

Identification	Type	VK10
	Part-No.	606157
Use/Area of application		
Application	<ul style="list-style-type: none"> • Electrotechnology, pneumatics, hydraulics, robotics, general machine and plant construction 	
Properties	<ul style="list-style-type: none"> • Feed through and terminal frames from high-quality solid • Aluminium or polyamide GF30 with additional inner brass reinforcement • High flexibility in the application • Additional mounting to existing installation easily possible • Even pressure effect on the feed through round material yields good strain relief and sealing • Unused holes in the module can simply sealed with blank plugs • Compact design i.e. space-saving • 2 module sizes with slot and suspension principle • Very good weathering resistance • Resistant to UV radiation, ozone, oils, fuels, acids, bases, solvents and sea water 	
Technical data		
Fire performance	Flame-retardant	
Temperature range	-40 °C to +135 °C	
Protection class	IP 65	

14.11.2013 – Subject to technical modification

Part-No. 606157

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
 www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet - Cablefix Vario

Feed-through for all prefabricated cables and wires with connectors

Module type	VG=40x43.5 VK=40x22.9 for cable and wire diameters from 4 mm to 34.5 mm, see ordering information frame sizes, see ordering information
Clamping range D	9.5 – 10.5 mm
Number of holes	3
Dimensions (w x h x d)	x 20.0 x mm

Design

Length	40.00 mm
--------	----------

General

PU	5 piece
Note	Unit corresponds to the number of required rubber modules type VK or VG

14.11.2013 – Subject to technical modification

Part-No. 606157

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY