



Main

| | |
|---------------------------|--|
| Contacteur application | Control circuit |
| Range of product | CT |
| Product or component type | Contacteur |
| Device short name | CT |
| Poles description | 2P |
| Pole contact composition | 2 NO |
| Network type | AC |
| Utilisation category | AC-1 conforming to IEC 60947-4 AC-3 conforming to IEC 60947-4 AC-5A conforming to IEC 60947-4 AC-5A conforming to IEC 61095 AC-5B conforming to IEC 60947-4 AC-5B conforming to IEC 61095 AC-7A conforming to IEC 61095 AC-7B conforming to IEC 61095 |
| Control type | Remote control |
| Control circuit voltage | 230/240 V AC 50 Hz |

Complementary

| | |
|--------------------------------|--|
| [Ie] rated operational current | 16 A AC-7A |
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 250 V AC 50 Hz |
| Maximum power | 2.1 kW 250 V AC |
| Control signal type | Maintained |
| Local signalling | Color indicator |
| Hold-in power consumption VA | 3.8 VA |
| Inrush power in VA | 9.2 VA |
| Mounting mode | Clip-on |
| Mounting support | 35 mm symmetrical DIN rail |
| 9 mm pitches | 2 |
| Height | 81 mm |
| Width | 18 mm |
| Depth | 60 mm |
| Colour | Grey |
| Electrical durability | 200000 cycles AC 50/60 Hz conforming to EN 60947-4-1 200000 cycles AC 50/60 Hz conforming to EN 61095 200000 cycles AC 50/60 Hz conforming to IEC 1095 |
| Connections - terminals | Power circuit : 2 tunnel type terminals 2.5 mm ² for flexible cable(s) Power circuit : 1 tunnel type terminals 6 mm ² for rigid cable(s) Control circuit : 2 tunnel type terminals 2.5 mm ² for flexible cable(s) Control circuit : 2 tunnel type terminals 1.5 mm ² for rigid cable(s) |
| Product compatibility | Auxiliary contact Interference filter Mixed control: impulse/latched Time delay |

Environment

| | |
|------------------------|-----------------------|
| Standards | EN 61095 IEC 61095 |
| Product certifications | CCC CEBEC GOST |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

IMQ
VDE

| | |
|---------------------------------------|--|
| Noise level | 30 dB |
| IP degree of protection | IP20 |
| Pollution degree | 2 |
| Tropicalisation | 2 conforming to EN 60947-4-1 2 conforming to EN 61095 2 conforming to IEC 1095 |
| Relative humidity | 95 % 55 °C |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | -5...60 °C |
| Ambient air temperature for storage | -40...60 °C |