



Main

Contactor application	Control circuit
Range of product	CT
Product or component type	Contactor
Device short name	CT
Poles description	2P
Pole contact composition	1 NO + 1 NC
Network type	AC
Utilisation category	AC-7B conforming to IEC 61095 AC-7A conforming to IEC 61095 AC-5B conforming to IEC 61095 AC-5B conforming to IEC 60947-4 AC-5A conforming to IEC 61095 AC-5A conforming to IEC 60947-4 AC-3 conforming to IEC 60947-4 AC-1 conforming to IEC 60947-4
Control type	Remote control
Control circuit voltage	12 V AC 50 Hz

Complementary

[Ie] rated operational current	16 A AC-7A
Network frequency	50 Hz
[Ue] rated operational voltage	250 V AC 50 Hz
Maximum power	2.1 kW 250 V AC
Control signal type	Maintained
Local signalling	Color indicator
Hold-in power consumption VA	3.8 VA
Inrush power in VA	15 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm
Colour	Grey
Electrical durability	200000 cycles AC 50/60 Hz conforming to IEC 1095 200000 cycles AC 50/60 Hz conforming to EN 61095 200000 cycles AC 50/60 Hz conforming to EN 60947-4-1
Connections - terminals	Control circuit: 2 tunnel type terminals 1.5 mm ² for rigid cable(s) Control circuit: 2 tunnel type terminals 2.5 mm ² for flexible cable(s) Power circuit: 1 tunnel type terminals 6 mm ² for rigid cable(s) Power circuit: 2 tunnel type terminals 2.5 mm ² for flexible cable(s)
Product compatibility	Auxiliary contact Interference filter Mixed control: impulse/latched Time delay

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	EN 61095 IEC 61095
Product certifications	CCC CEBEC GOST IMQ VDE
Noise level	30 dB
IP degree of protection	IP20
Pollution degree	2
Tropicalisation	2 conforming to IEC 1095 2 conforming to EN 61095 2 conforming to EN 60947-4-1
Relative humidity	95 % 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-40...60 °C

Contractual warranty

Period	18 months
--------	-----------