A9A26946

voltage release - iMX+OF - tripping unit - 220..415 VAC



Main

Range	Acti 9
Product or component type	Shunt trip release with OC contact
Device short name	IMX+OF
Signal contacts composition	1 C/O
[le] rated operational current	AC-12: 3 A AC 50 Hz 415 V AC-12: 6 A AC 50 Hz 100 V AC-12: 6 A AC 50 Hz 230 V DC-12: 1 A DC 110 V DC-12: 1 A DC 130 V
Control circuit voltage	100 V AC 50/60 Hz 110 V DC 130 V DC 230 V AC 50/60 Hz 415 V AC 50/60 Hz
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigi ARA RCA

Complementary

Local signalling	Action indicator	
Mounting mode	Clip-on	
Mounting support	DIN rail	
Width	18 mm	
Colour	White	
Connections - terminals	Clamp terminal 2 cable(s) 2.5 mm² flexible with cable end Clamp terminal 1 cable(s) 6 mm² rigid Clamp terminal 2 cable(s) 2.5 mm² rigid Clamp terminal 1 cable(s) 4 mm² flexible	
Tightening torque	1 N.m	

Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-2550 °C
Ambient air temperature for storage	-4085 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1216 - Schneider Electric declaration of conformity

Contractual warranty

Contractual Wallanty		
Period	18 months	