



### Main

Range	Acti 9
Product or component type	OC contact
Device short name	iOF
Signal contacts composition	1 C/O
[Ie] rated operational current	1 A DC 130 V 3 A AC 50/60 Hz 415 V 1.5 A DC 60 V 2 A DC 48 V 6 A DC 24 V 6 A AC 50/60 Hz 240 V
9 mm pitches	1

### Complementary

[Ui] rated insulation voltage	4 kV
Mounting mode	Clip-on
Mounting support	DIN rail
Height	86 mm
Width	9 mm
Depth	73 mm
Product weight	32 g
Colour	White
Connections - terminals	Screw clamp terminal 2 rigid cable(s) 2.5 mm <sup>2</sup> max Screw clamp terminal 2 flexible cable(s) 1.5 mm <sup>2</sup> max with cable end Screw clamp terminal 1 flexible cable(s) 0.5...2.5 mm <sup>2</sup> max Screw clamp terminal 1 rigid cable(s) 1...4 mm <sup>2</sup> max
Wire stripping length	10 mm
Tightening torque	1 N.m
Product compatibility	IC60 IID Single terminal ISW-NA IDPN Vigj ARA RCA

### Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1216 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Available

### Contractual warranty

Period	18 months
--------	-----------

