



Main

Range	Acti 9
Product or component type	Fault contact
Device short name	ISD
Signal contacts composition	1 C/O
[Ie] rated operational current	1 A DC 130 V 3 A AC 50/60 Hz 415 V 1.5 A DC 60 V 2 A DC 48 V 6 A DC 24 V 6 A AC 50/60 Hz 240 V
9 mm pitches	1

Complementary

[Ui] rated insulation voltage	4 kV
Local signalling	Mechanical indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Height	86 mm
Width	9 mm
Depth	73 mm
Product weight	33 g
Colour	White
Connections - terminals	Screw clamp terminal 2 rigid cable(s) 2.5 mm ² max Screw clamp terminal 2 flexible cable(s) 1.5 mm ² max with cable end Screw clamp terminal 1 flexible cable(s) 0.5...2.5 mm ² max Screw clamp terminal 1 rigid cable(s) 1...4 mm ² max
Wire stripping length	10 mm
Tightening torque	1 N.m
Product compatibility	IC60 IID Single terminal ISW-NA IDPN Vigii ARA RCA

Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1216 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

