



Main

| | |
|--------------------------------|-------------------------------------|
| Range of product | NSX100...250 |
| Circuit breaker application | Motor protection |
| Poles description | 3P |
| Protected poles description | 3t |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Trip unit name | MA |
| Trip unit technology | Magnetic |
| Trip unit protection functions | I |
| Trip unit rating | 50 A (65 °C) |
| Protection type | Short-circuit protection (magnetic) |

Complementary

| | |
|---|-----------------------|
| Mounting mode | Fixed |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Short-time pick-up adjustment type Isd | Adjustable 9 settings |
| [Isd] short-time pick-up adjustment range | 6...14 x In |

Environment

| | |
|---------------------------------------|---|
| Standards | EN 60947-2 IEC 60947-2 NEMA AB1 UL 508 |
| Product certifications | CSA UL |
| IP degree of protection | IP40 conforming to IEC 60529 |
| Pollution degree | 3 conforming to IEC 60947-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS | Compliant - since 0819 - Schneider Electric declaration of conformity |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |