



Main

Range of product	NSX100...250 NSX400...630 Easypact CVS100...250 Easypact CVS400...630 NSX100...250 DC NSX400...630 DC PowerPact multistandard
Product or component type	Voltage release
Device short name	MX
Voltage release type	Shunt trip release
Control circuit voltage	48 V DC

Complementary

Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Threshold tripping voltage	0.7...1.1 x Un - during opening time
Supply inrush power	30 VA
Mounting mode	Fixed
Response time	50 ms
Auxiliary connection terminal	Screw terminal <= 1.5 mm ²

Environment

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0938 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.