

# LV431540

motor-mechanism - MT250 - SDE adaptor - 110..130 V AC 50/60Hz



## Main

Range of product	NSX100...250 Easypact CVS100...250 NSX100...250 DC PowerPact multistandard
Product or component type	Motor mechanism
Product compatibility	PowerPact H-Frame PowerPact J-Frame
[In] rated current	250 A
Control circuit voltage	110...130 V AC 50/60 Hz

## Complementary

Control type	Standard
Control signal type	Impulse Maintained
Mounting mode	Fixed
Response time	< 600 ms - during opening time < 80 ms - during closing time
Maximum operating frequency	4 per minute
Power consumption in VA	<= 500 VA - during closing time <= 500 VA - during opening time
Provided equipment	SDE adaptor
Locking options description	1 to 3 padlocks Ø 5 to Ø 8 Padlocking in OFF position

## Environment

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0909 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Available

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.