

Main

Range of product	Enclosed Interpact
Product or component type	Enclosed switch-disconnector
[Ue] rated operational voltage	690 V
[Ie] rated operational current	160 A
Handle colour	Black

Complementary

Mechanical interlocking	Door interlocking function
Poles description	3P + N
Network type	AC
Network frequency	50/60 Hz
Utilisation category	AC-23A
Connections - terminals	Flat pads for crimped lug
Control type	Rotary handle
Handle front plate colour	Black
Provision for padlocking	Handle padlockable in on and off position
Enclosure material	Sheet steel epoxy-polyester powder beige
IP degree of protection	IP55 BS EN 60529
Standards	BS EN 60947-3
Provided equipment	Removable bottom gland plate
Contact position indicator	Yes
Suitability for isolation	Yes

Environment

Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.