



Main

Range	Linergy
Product name	FM
Product or component type	Distribution block

Complementary

Mounting support	DIN rail Plain backplate Slotted backplate
Mounting mode	By screws Clip-on
Range compatibility	Prisma - G Prisma - P Pragma Prisma - PH Spacial Kaedra TeSys
Product compatibility	Spacial enclosures
Poles description	2P
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	200 A
[Ipk] rated peak withstand current	20 kA
I ² t on activation	6700000 A ² .s
Connections - terminals	Supply: flexible bars, 20 x 3 mm Supply : crimped lug 50 mm ² Distribution : quick-connect terminal strips (phase) , 12 x 10 mm ² (flexible) Distribution : quick-connect terminal strips (phase) , 12 x 10 mm ² (rigid) Distribution : quick-connect terminal strips (neutral) , 12 x 10 mm ² (flexible) Distribution : quick-connect terminal strips (neutral) , 12 x 10 mm ² (rigid)

Environment

IP degree of protection	IPxx B
Standards	IEC 61439-1 inside Prisma IEC 61439-2 inside Prisma IEC 60947-7-1
Product certifications	ASEFA KEMA

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0835 - Schneider Electric declaration of conformity
Product environmental profile	Available

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

