



### Main

Range	Linergy
Product name	DP
Product or component type	Distribution block

### Complementary

Mounting support	DIN rail Prisma mounting plate
Range compatibility	Prisma - G Prisma - P Compact Prisma - PH Spacial TeSys
Product compatibility	Spacial enclosures
Installed device	NSX100...250 with earth leakage protection NSX100...250 without earth leakage protection INS250 INS250 lateral handle vertical installation INV250 INV250 lateral handle vertical installation
Poles description	3P
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	250 A
[Icw] rated short-time withstand current	8.5 kA 1 s
[Ipk] rated peak withstand current	30 kA
I <sup>2</sup> t on activation	72250000 A <sup>2</sup> .s
Connections - terminals	Supply: direct connection Distribution: spring terminal (phase) , 6 x 1...10 mm <sup>2</sup> (flexible) Distribution: spring terminal (phase) , 3 x 1...16 mm <sup>2</sup> (flexible) Distribution: spring terminal (phase) , 6 x 1...10 mm <sup>2</sup> (rigid) Distribution: spring terminal (phase) , 3 x 1...16 mm <sup>2</sup> (rigid)
Height	105 mm
Width	138 mm
Depth	63 mm

### Environment

Pollution degree	3
Overvoltage category	III
IP degree of protection	IPxx B
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11
Standards	IEC 61439-2

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Product certifications	ASEFA KEMA
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	40 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0810 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations