



Main

Range	Linergy
Product name	BS
Product or component type	Distribution block

Complementary

Mounting support	Plain backplate Slotted backplate Prisma upright
Mounting mode	Horizontal Vertical
Range compatibility	Prisma - G Prisma - P Prisma - PH Prisma - Pack Spacial TeSys
Product compatibility	Spacial enclosures
Poles description	4P
[Ue] rated operational voltage	440 V AC
[Ui] rated insulation voltage	750 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	160 A
[Icw] rated short-time withstand current	10 kA 1 s
[Ipk] rated peak withstand current	30 kA
I ² t on activation	100000000 A ² .s
Busbar cross section	15 x 5 mm
Connections - terminals	Supply: crimped lug 16...50 mm ² Distribution: M6 holes (phase) , 13 x <= 50 mm ² Supply: flexible bars, 20 x 2 mm
Height	235 mm
Width	470 mm
Depth	115 mm

Environment

IP degree of protection	IPxx B
Standards	IEC 61439-2
Product certifications	ASEFA KEMA

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0819 - Schneider Electric declaration of conformity
Product environmental profile	Available

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

