



Main

Range	Linergy
Product name	BW
Product or component type	Busbar
Busbar description	Insulated bar
Provided equipment	Clip-on covers

Complementary

Range compatibility	Prisma - G Prisma - P
Poles description	4P
Busbar position	Rear
Installation direction	Vertical
Enclosure/cubicle description	Pack enclosure Cubicle: 650 mm Floor-standing enclosure: 600 mm Wall-mounted enclosure: 600 mm Wall-mounted duct: 300 mm Floor-standing duct: 300 mm
[Ui] rated insulation voltage	750 V
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	160 A
[Icw] rated short-time withstand current	10 kA (1 s)
[Ipk] rated peak withstand current	30 kA
I ² t on activation	100000 kA ² .s
Permissible current	160 A
Length	1000 mm
Type of busbar connection	M6 threaded hole
Connection pitch	Connection each 25 mm

Environment

IP degree of protection	IPxx B
Standards	IEC 61439-2
Product certifications	ASEFA KEMA

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0807 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations