



Main

Range of product	Prisma Plus System G
Product or component type	Duct
Number of vertical modules (50 mm)	12

Complementary

Enclosure/cubicle description	Wall-mounted duct: 300 mm
[Ui] rated insulation voltage	1000 V on main rear busbars conforming to IEC 60439-1
[Ie] rated operational current	630 A at 40 °C conforming to IEC 60439-1
[Icw] rated short-time withstand current	25 kA (1 s) conforming to IEC 60439-1
[Ipk] rated peak withstand current	53 kA conforming to IEC 60439-1
Network frequency	50/60 Hz
Additional information	Can be combined side by side and one on top of another
Height	630 mm
Width	300 mm
Depth	205 mm
Colour	White RAL 9001

Environment

IP degree of protection	IP30 with or without door IP31 with door and canopy IP43 with door, canopy and IP43 gasket
IK degree of protection	IK07 without door IK08 with door
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Standards	IEC 60439-1 IEC 62208

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0832 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations