



### Main

Range	Multi 9
Product or component type	Fault contact
Device short name	SD
Signal contacts composition	1 C/O
[Ie] rated operational current	1 A DC 130 V 1.5 A DC 60 V 2 A DC 48 V 6 A DC 24 V 3 A AC 50/60 Hz 380...415 V 6 A AC 50/60 Hz 220...240 V
9 mm pitches	1

### Complementary

Mounting mode	Fixed
Mounting support	DIN rail
Height	84 mm
Width	9 mm
Depth	73 mm
Connections - terminals	Clamp terminal 1 flexible cable(s) 2.5 mm <sup>2</sup> max Clamp terminal 1 rigid cable(s) 2.5 mm <sup>2</sup> max Clamp terminal 2 flexible cable(s) 1.5 mm <sup>2</sup> max Clamp terminal 2 rigid cable(s) 1.5 mm <sup>2</sup> max
Wire stripping length	9 mm
Tightening torque	1 N.m
Product compatibility	C60 IDPN C120 ID I-NA

### Environment

Standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.