

CCT15722

Acti 9 - IHP - 2C digital time switch - 24 hours + 7 days



Main

Range of product	Acti 9
Modular device name	IHP
Device short name	IHP 2c
Product or component type	Programmable digital time switch
Product compatibility	Mechanical compatibility with electrical distribution comb busbars
Number of channels	2
Battery type	Lithium
Function available	Automatic winter/summer time changeover
Type of setting	Absence for holidays function
Language	English French German Italian Portuguese Spanish

Complementary

Device application	Building
Cycle duration	24 hours + 7 days
Maximum number of switchings	56
Minimum interval duration	1 min
Accuracy	+/- 1 s/day 20 °C
Power consumption	7 VA
Maximum switching current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
[Ue] rated operational voltage	230 V (+/- 10 %) AC 50/60 Hz
Display type	Backlit LCD
Battery life	6 yr
Backup time	6 years time and program saving
Product mounting	DIN rail
9 mm pitches	5
Colour tint	White (RAL 9003)
Connections - terminals	Screwless terminals
Width	45 mm
Height	85 mm
Depth	66 mm

Environment

Ambient air temperature for operation	-10...50 °C
IP degree of protection	IP20 B

Offer Sustainability

Sustainable offer status	3303431062867
Product environmental profile	3303431062867
Product end of life instructions	3303431062867

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.