



Main

Range of product	Prisma Plus System G - floor-standing enclosure: 600 mm Prisma Plus System G - wall-mounted enclosure: 600 mm Prisma Plus System G - floor-standing enclosure: 850 mm
Product or component type	Mounting plate
Installed device	Compact: fixed NSX100...250 - control: toggle - horizontal installation Interpact: fixed INS250 - control: direct front rotary handle - horizontal installation Interpact: fixed INV250 - control: direct front rotary handle - horizontal installation
Poles description	1 x 3P 1 x 4P

Complementary

Colour	White RAL 9001
--------	----------------

Environment

Standards	IEC 61439-2
Product certifications	ASEFA KEMA

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0807 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.