



Main

Range of product	Prisma Plus System P - cubicle : 650 mm Prisma Plus System G - floor-standing enclosure : 600 mm Prisma Plus System G - wall-mounted enclosure : 600 mm
Product or component type	Front plate
Type of front plate	Modular Cut-out
Installed device	Multi 9 : fixed modular device Acti 9 : fixed modular device Interpact : fixed INS40...160

Complementary

Number of vertical modules (50 mm)	4
Height	200 mm
Width	500 mm
Colour	White RAL 9001

Environment

Standards	IEC 61439-2
Product certifications	ASEFA KEMA

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0701 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.