



### Main

Range of product	Prisma Plus System P - cubicle : 650 mm
Product or component type	Front plate
Type of front plate	Cut-out
Installed device	Compact : fixed NSX400...630 without earth leakage protection - horizontal installation Compact : plug-in NSX400...630 with earth leakage protection - control: direct front rotary handle - horizontal installation Compact : plug-in NSX400...630 without earth leakage protection - horizontal installation Compact : fixed NSX400...630 with earth leakage protection - control: toggle - horizontal installation Compact : plug-in NSX400...630 with earth leakage protection - control: toggle - horizontal installation Compact : fixed NSX400...630 with earth leakage protection - control: direct front rotary handle - horizontal installation
Poles description	1 x 4P

### Complementary

Number of vertical modules (50 mm)	5
Height	250 mm
Colour	White RAL 9001

### Environment

Standards	IEC 61439-2
Product certifications	ASEFA KEMA

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0751 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.