

A9A15416

Extra low voltage relay iRTBT - 10mA/10VDC -
5A/250VAC - 12...24 VAC/DC



Main

Relay application	Extra low voltage interface relay
Function available	Actuation of LV circuits based on an extra low voltage order
Range of product	IRTBT
Device short name	IRTBT
Signal contacts composition	1 C/O
Control circuit voltage	12...24 V AC 12...24 V DC

Complementary

[Ie] rated operational current	5 A AC 250 V 0.01 A DC 10 V
[Ui] rated insulation voltage	4000 V
Local signalling	Green LED for power on
Supply holding power	0.22 W
Supply inrush power	0.11 W
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Colour	White
Electrical durability	100000 cycles
Connections - terminals	Tunnel type terminals

Environment

Offer Sustainability

Sustainable offer status	3606480097720
RoHS	Compliant - since 1312 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.