



Main

Range of product	CT
Device short name	ACTo+f
Product or component type	Remote indication auxiliary
Signal contacts composition	1 NO + 1 NC

Complementary

[I _e] rated operational current	1 A DC 130 V 2 A AC 50/60 Hz 240 V 0.01 A DC 24 V 0.01 A AC 24 V
Mounting mode	Fixed, on the right of CT
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	1
Height	81 mm
Width	9 mm
Depth	60 mm
Colour	Grey
Auxiliary connection terminal	Tunnel type terminals 2 cable(s) flexible 2.5 mm ² Tunnel type terminals 2 cable(s) rigid 1.5 mm ²
Product compatibility	CT association on right side

Environment

Standards	EN 60947-5
Tropicalisation	2
Relative humidity	95 % (55 °C)
Ambient air temperature for operation	-20...50 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.