



Main

Range	PowerLogic
Product name	CT
Product or component type	Current transformer
Secondary current	5 A
Accuracy class	Class 0.5 maximum power: 4 VA Class 3 maximum power: 6 VA Class 1 maximum power: 5.5 VA
[In] rated current	200 A

Complementary

Current transformer type	Tropicalised for cable
Current transformer ratio	200/5
Safety factor	<= 5
[Ue] rated operational voltage	< 720 V AC at 50/60 Hz
Mounting support	DIN rail Mounting plate
Width	44 mm outside
Height	65 mm outside
Depth	30 mm outside
Diameter	21 mm
Product weight	0.2 kg
Cable outer diameter	<= 21 mm max <= 120 mm ²
Sealing	With

Environment

Standards	IEC 60044-1 VDE 0414
IP degree of protection	IP20
Relative humidity	>= 95 %
Ambient air temperature for operation	-25...60 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0610 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.