



Main

| | |
|---------------------------|--|
| Range of product | Acti 9 |
| Device short name | IC2000P+ |
| Product or component type | Programmable twilight switch with time switch function |
| Battery type | Lithium |
| Function available | Automatic time changeover Coupling with time switch functions |
| Language | Dutch English Finnish French German Italian Portuguese Spanish Swedish |
| Type of setting | Weekly programming |

Complementary

| | |
|--------------------------------|---|
| Device application | Building |
| Measurement accuracy | < +/- 1 s/day |
| Number of channels | 1 |
| Control type | By brightness detection |
| Provided equipment | Wall-mounted cell |
| Load type | 230 V AC halogen lamp, (2300 W) 230 V AC incandescent lamp, (2300 W) Non-corrected fluorescent tube, balast : conventional, (10 x 100 W) Parallel-corrected fluorescent tube, balast : conventional, (10 x 36 W) Serial-corrected fluorescent tube, balast : conventional, (10 x 100 W) Parallel-corrected fluorescent tube, balast : conventional, (2 x 100 W) Non-corrected fluorescent tube, balast : conventional, (20 x 58 W) Serial-corrected fluorescent tube, balast : conventional, (20 x 58 W) Non-corrected fluorescent tube, balast : conventional, (26 x 36 W) Serial-corrected fluorescent tube, balast : conventional, (26 x 36 W) Fluorescent tube, balast : electronic, (6 x 58 W) Parallel-corrected fluorescent tube, balast : conventional, (6 x 58 W) Fluocompact lamp, balast : electronic, (7 x 11 W) Fluocompact lamp, balast : electronic, (7 x 15 W) Fluocompact lamp, balast : electronic, (7 x 20 W) Fluocompact lamp, balast : electronic, (9 x 7 W) Fluorescent tube, balast : electronic, (9 x 36 W) Dual mounted fluorescent tube, balast : conventional, (26 x 36 W) Dual mounted fluorescent tube, balast : conventional, (20 x 58 W) Dual mounted fluorescent tube, balast : conventional, (10 x 100 W) Parallel-corrected mercury and sodium vapour lamps, (250 VA) Dual mounted fluorescent tube, balast : electronic, (5 x (2 x 36 W)) Dual mounted fluorescent tube, balast : electronic, (3 x (2 x 58 W)) |
| Power consumption | 3 VA |
| Maximum switching current | 10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1 |
| [Ue] rated operational voltage | 230 V (+10 % -15 %) AC 50/60 Hz |
| Display type | Backlit LCD |
| Time delay | |
| Maximum number of switchings | 42 |
| Minimum interval duration | 1 min |
| Backup time | 5...6 years time and program saving |
| Mounting support | DIN rail |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|-----------------------------|--|
| 9 mm pitches | 5 |
| Light intensity adjustment | 2...50 lux 350...2100 lux 60...300 lux |
| Connections - terminals | X 1 screw terminal : <= 6 mm ² |
| Cable stiffness | Flexible Rigid |
| Electrical insulation class | Class II |
| Height | 83.5 mm |
| Width | 45 mm |
| Depth | 65 mm |
| Product weight | 323 g |

Environment

| | |
|---------------------------------------|------------------------|
| Standards | EN 60529 EN 60730-1 |
| Ambient air temperature for operation | -20...50 °C |
| IP degree of protection | IP20 B |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | 3303430154839 |
| RoHS | Compliant - since 0519 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |