



Main

Range	Multi 9
Product or component type	Undervoltage release
Device short name	MN
Control circuit voltage	220...240 V AC 50/60 Hz
Control type	Standard
9 mm pitches	2
Product compatibility	C60 IDPN C120 DPN

Complementary

Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Connections - terminals	Clamp terminal 1 cable(s) 2.5 mm ² flexible Clamp terminal 1 cable(s) 2.5 mm ² rigid Clamp terminal 2 cable(s) 1.5 mm ² flexible Clamp terminal 2 cable(s) 1.5 mm ² rigid
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA ASTA KEMA LCIE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.