

Interlock extension

ZVV-T0



Article no.

Part no.

022298

Up to four off, 25 mm each, can be plugged onto interlock section

(An equal number of shaft extensions is required for this purpose)

Program				
Range	Accessories			
	Interlock elements			
Information about equipment supplied	A max. of 4 units can be put on the interlock section every 25 required for this)	mm (an		
	Use only with T0/T3 and P1/Z designs			
For use with	UV-T0			

## Approbationen UL approval CSA approval

N N

## Technical data according to FTIM 4.0

echnical data according to ETIM 4.0		
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as normally closed contact		0
Rated permanent current lu	А	0
Number of poles		0
Conditioned rated short-circuit current lq	kA	0
Degree of protection (IP), front side		-
Number of auxiliary contacts as change-over contact		0
Interlockable		No
Motor drive integrated		No
Connection type main current circuit		-
Version as emergency stop installation		No
Type of control element		-
Version as main switch		No
Version as switch disconnector compact		No
Version as safety switch		No
Version as maintenance-/service switch		No
Rated operation power at AC-23, 400V	kWh	0
Rated operation power AC-3, 400 V	kWh	0
Suitable for ground mounting		No
Suitable for front mounting		No
Suitable for front mounting center		No
Suitable for distribution board installation		No
Suitable for intermediate mounting		No
Max. rated operation voltage Ue AC	V	0
Motor drive optional		No
Voltage release optional		No
Device construction		-

## Additional product information (links)

Engineering	
Technical overview	$ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Ovt\_t\_p\_Leistung\_G.pdf$
Key to part numbers, modular system	$ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Ovt\_t\_p\_Typenschluessel\_G.pdf$
Ordering of non-standard switches	ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Bestellformulare_de.pdf