



Miniature circuit-breaker



Powering Business Worldwide™

Part no. FAZ-D4/1

Article no. 278576

Approbationen

UL approval	Yes
CSA approval	Yes
Product Standards	IEC/EN 60947-2; IEC/EN 60898; UL 1077; CSA-C22.2 No. 235; CE marking
UL File No.	E177451
UL CCN	QVNU2, QVNU8
CSA File No.	204453
CSA Class No.	3215-30
NA Certification	UL recognized, CSA certified
Conditions of Acceptability	Supplementary Protector only
Suitable for	Branch Circuits; not as BCPD
Current Limiting CB	No
Max. Voltage Rating	277 VAC; 48 VDC
Degree of Protection	IEC: IP20; UL/CSA Type: -

Technical data according to ETIM 4.0

Frequency	Hz	50 Hz
Voltage type		AC
Mounting depth	mm	71 mm
Rated current	A	4 A
Rated voltage	V	230 V
Trip type		D
Number of poles		1
Current-limiting class		3
Overvoltage category		3
Pollution degree		2
Width in space units		1
Protection type (IP)		IP20
Neutral conductor switching with pole		false
Rated switching capacity according to EN 60898	kA	10 kA
Rated switching capacity according to IEC 60947-2	kA	0 kA
Additional equipment possible		true