



Terminal shroud



Powering Business Worldwide™

Part no.
Article no.

H-P3
021999

Program

Range			Accessories
			Protective covers
			For covering the connection terminals on 3 pole open switch-disconnectors with N neutral conductor and/or HI11 auxiliary contact
For use with			P3-.../E, .../Z, .../EA, .../V P3-...N, ...HI11, ...N...HI11
Notes			
The shroud is designed for fitting onto both sides of the switch-disconnector. Parts which are not required can be broken off.			

Approbationen

UL approval	N
CSA approval	N

Technical data according to ETIM 4.0

Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			0
Rated permanent current I _u		A	0
Number of poles			0
Conditioned rated short-circuit current I _q		kA	0
Degree of protection (IP), front side			-
Number of auxiliary contacts as change-over contact			0
Interlockable			No
Motor drive integrated			No
Connection type main current circuit			-
Version as emergency stop installation			No
Type of control element			-
Version as main switch			No
Version as switch disconnector compact			No
Version as safety switch			No
Version as maintenance-/service switch			No
Rated operation power at AC-23, 400V		kWh	0
Rated operation power AC-3, 400 V		kWh	0
Suitable for ground mounting			No
Suitable for front mounting			No
Suitable for front mounting center			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			No
Max. rated operation voltage U _e AC		V	0
Motor drive optional			No
Voltage release optional			No
Device construction			-

Additional product information (links)

Engineering

Technical overview	ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Ovt_t_p_Leistung_G.pdf
Key to part numbers, modular system	ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Ovt_t_p_Typenschlüssel_G.pdf
Ordering of non-standard switches	ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Bestellformulare_de.pdf