Part no.	
Article no.	

ZVV-P3

024671



Up to four off, 25 mm each, can be plugged onto interlock section

(An equal number of shaft extensions is required for this purpose)

Program			
Range			Accessories
			Interlock elements
Information about equipment supplied			A max. of 4 units can be put on the interlock section every 25 mm (an equal number of shaft extensions is required for this)
			Use only with T5(B)/Z and P3/Z designs
For use with			UV-P3
Approbationen			
UL approval CSA approval	N N		
Fechnical data according to ETIM 4.0			
Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			0
Rated permanent current lu	A	4	0
Number of poles			0
Conditioned rated short-circuit current Iq	k	κA	0
Degree of protection (IP), front side			-
Number of auxiliary contacts as change-over contact			0
Interlockable			No
Motor drive integrated			No
Connection type main current circuit			
Version as emergency stop installation			No
Type of control element			-
Version as main switch			No
Version as switch disconnector compact			No
Version as safety switch			No
Version as maintenance-/service switch			No
Rated operation power at AC-23, 400V	k	Wh	0
Rated operation power AC-3, 400 V	k	Wh	0
Suitable for ground mounting			No
Suitable for front mounting			No
Suitable for front mounting center			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			No
Max. rated operation voltage Ue AC	V	/	0
Motor drive optional			No
Voltage release optional			No
Device construction			-

Additional product information (links)

Engineering		
	Technical overview	$ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/0vt_t_p_Leistung_G.pdf$
	Key to part numbers, modular system	$ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Ovt_t_p_Typenschluessel_G.pdf$
	Ordering of non-standard switches	ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Bestellformulare_de.pdf