



Plug-in extens.shaft can be cut



Powering Business Worldwide™

Part no. PKZ2-XAH
Article no. 106129

Can be extended as required for mounting depths from 171 - 300 mm

Program

			Can be extended as required for mounting depths from 171 – 300 mm
--	--	--	---

Approbationen

UL approval	Yes
CSA approval	Yes
Product Standards	UL 508; CSA-C22.2 No. 14; IEC60947-4-1; CE marking
UL File No.	E36332
UL CCN	NLRV
CSA File No.	12528
CSA Class No.	3211-05
NA Certification	UL listed, CSA certified
Specially designed for NA	No

Technical data according to ETIM 4.0

Cross-section width		mm	5
Cross-section height		mm	5
Length		mm	183

Additional product information (links)

AWA1280-2368 Door coupling rotary handle	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/23681108.pdf
Motor starters and "Special Purpose Ratings" for the North American market	http://www.moeller.net/binary/ver_techpapers/ver953en.pdf
Busbar Component Adapters for modern Industrial control panels	http://www.moeller.net/binary/ver_techpapers/ver960en.pdf
PKZ 2 System - For Optimum Motor and System Protection	http://www.moeller.net/binary/ver_techpapers/ver952en.pdf