



Main switch assembly kit red/yellow



Powering Business Worldwide™

Part no. NZM1-XHBR

Article no. 266632

Equipment supplied:

- Rotary door-coupling handle
- NZM...-XV4 extension shaft
- External warning plate/designation label in German/English
- Black and yellow flash

For enhanced protection against direct contact on the incomer side, IP2X protection against contact with a finger can be ordered → 266744

☞ Other external warning plates/designation labels can be clipped on.

Program

Equipment supplied			Door coupling rotary handle with rotary drive NZM...-XV4 extension shaft External warning plate/marketing plate in German/English Black and yellow lightning symbol
Function			With red door coupling rotary handle for use of switch as emergency switching off device to IEC/EN 60204-1, VDE 0113 part 1
Protection class			IP66 UL/CSA Type 4X, Type 12
Locking facility			lockable on the 0 position on the handle using up to 3 padlocks With door interlock lockable on the switch in the 0 position
Project planning information			External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger.
For use with			NZM1(-4) PN1(-4), N(S)1(-4)

Approbationen

UL approval	Yes
CSA approval	Yes
Product Standards	UL489; CSA-C22.2 No. 5-09; IEC60947, CE marking
UL File No.	E140305
UL CCN	DIHS
CSA File No.	022086
CSA Class No.	1437-01
NA Certification	UL listed, CSA certified
Degree of Protection	IEC: IP66, UL/CSA Type 4X, 12

Technical data according to ETIM 4.0

Suitable for switch-disconnector			YES
Suitable for circuit-breakers			YES
With shaft			YES
Suitable for emergency switching off			YES
Lockable			YES
Color			red

Additional product information (links)

AWA1230-2055 (IL01219050Z) Main switch assembly kit	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/20550410.pdf
IL01203005Z (IL01203005Z) Door coupling rotary handle	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL01203005Z2010_11.pdf