



Lock-out handle for padlocks

Part no. SVB-T0

Article no. 057892



Powering Business Worldwide™

With red rotary handle and yellow locking collar

For locking the Off position

Lockable in the 0 (Off) position

For switches with positions 0 - I at 90° Switching angle, as front plate: FS908

Program

Range			Accessories
			Main switch assembly kits
Emergency stop			As an emergency switching off/emergency stop device
Standards			According to IEC/EN 60204-1, VDE 0113 Part 1
			Padlocking feature only for main switch Permissible with T0 with up to max. 4 contact units Permissible with T3 with up to max. 6 contact units
Type			With red rotary handle and yellow locking ring
For use with			T0-.../E, .../Z, .../I1 T3-.../E, .../Z, .../I2 P1-.../E, .../Z, .../I2
Notes			
<ul style="list-style-type: none"> • for interlocking the 0 position • for switches with positions 0 - I at 90° • Switching angle as front plate FS908 • Lockable with max. 3 padlocks 			

Approbationen

UL approval	N
CSA approval	N

Technical data according to ETIM 4.0

Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as normally closed contact			0
Rated permanent current I _u		A	0
Number of poles			0
Conditioned rated short-circuit current I _q		kA	0
Degree of protection (IP), front side			-
Number of auxiliary contacts as change-over contact			0
Interlockable			No
Motor drive integrated			No
Connection type main current circuit			-
Version as emergency stop installation			YES
Type of control element			-
Version as main switch			YES
Version as switch disconnecter compact			No
Version as safety switch			No
Version as maintenance-/service switch			YES
Rated operation power at AC-23, 400V		kWh	0
Rated operation power AC-3, 400 V		kWh	0
Suitable for ground mounting			No
Suitable for front mounting			No
Suitable for front mounting center			No
Suitable for distribution board installation			No
Suitable for intermediate mounting			No
Max. rated operation voltage U _e AC		V	0

Motor drive optional		No
Voltage release optional		No
Device construction		-

Dimensions

Up to 3 padlocks

Additional product information (links)

Engineering

Technical overview	ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Ovt_t_p_Leistung_G.pdf
Key to part numbers, modular system	ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Ovt_t_p_Typenschlüssel_G.pdf
Ordering of non-standard switches	ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Bestellformulare_de.pdf