

Extension shaft

Powering Business Worldwide™

Part no. ZAV-P3 Article no. 029417

Up to four off, 25 mm each, can be plugged onto switch shaft

	ra	

•	
Range	Accessories
	shaft extension
Information about equipment supplied	A max. of 4 units can be put on the switch shaft every 25 mm
For use with	T5(B)/Z P3/Z P3/V

N N

Approbationen
UL approval
CSA approval

Technical data according to FTIM 4.0

Number of auxiliary contacts as normally closed contact Rated permanent current lu Number of poles Conditioned rated short-circuit current lq Begree of protection (IP), front side Number of auxiliary contacts as change-over contact No control contact as a change-over contact No control element Version as memeraney stop installation No control element Version as safety switch No control element No control	Number of auxiliary contacts as normally open contact		0
Rated permanent current lu Number of poles Conditioned rated short-circuit current lq Degree of protection (IP), front side Number of auxiliary contacts as change-over contact Interlockable Motor drive integrated Connection type main current circuit Version as emergency stop installation Version as safety switch Version as safety switch Version as maintenance-/service switch Rated operation power at AC-23, 400V Suitable for ground mounting Suitable for front mounting Suitable for front mounting Suitable for front mounting Suitable for intermediate mounting Max. rated operation voltage Ue AC Motor drive optional Voltage release optional Versional Suitage release optional Voltage release optional Versional Suitage release optional			0
Number of poles 8 0 Conditioned rated short-circuit current Iq 8A 0 Degree of protection (IP), front side 2 - Number of auxiliary contacts as change-over contact 6 0 Interlockable No No Motor drive integrated 6 No Connection type main current circuit 6 No Version as emergency stop installation 6 No Version as main switch 7 No Version as main switch disconnector compact 8 No Version as switch disconnector compact No No Version as safety switch No No Version as maintenance-/service switch No No Rated operation power at AC-23, 400V kWh 0 Sated operation power at AC-23, 400V kWh 0 Suitable for front mounting No No Suitable for front mounting center No No Suitable for distribution board installation No No Max. rated operation voltage Ue AC N	· · ·	Α	0
Conditioned rated short-circuit current Iq kA 0 Degree of protection (IP), front side - - Number of auxiliary contacts as change-over contact B - No Interlockable No No No Connection type main current circuit - No - Version as emergency stop installation No - - Type of control element No No - Version as switch disconnector compact No No Version as safety switch No No Version as maintenance-/service switch No No Rated operation power at AC-23, 400V KWh 0 Rated operation power AC-3, 400 V kWh 0 Suitable for front mounting No No Suitable for front mounting center No No Suitable for distribution board installation No No Suitable for intermediate mounting No No Max. rated operation voltage Ue AC No No Motor drive optional No </td <td>•</td> <td></td> <td></td>	•		
Degree of protection (IP), front side Number of auxiliary contacts as change-over contact Interlockable Motor drive integrated Connection type main current circuit Version as emergency stop installation Type of control element Version as main switch Version as safety switch Version as safety switch Version as maintenance-/service switch Rated operation power at AC-23, 400 V Rated operation power AC-3, 400 V Suitable for ground mounting Suitable for front mounting Suitable for front mounting center Suitable for distribution board installation Max. rated operation voltage Ue AC Motor drive optional Versional Motor drive optional Version as safety switch No Suitable for intermediate mounting Motor drive optional Version as safety switch No No No No No No No No No N	·	kA	
Number of auxiliary contacts as change-over contact Interlockable Motor drive integrated Connection type main current circuit Version as emergency stop installation Type of control element Version as switch disconnector compact Version as switch disconnector compact Version as safety switch Version as maintenance-/service switch Rated operation power at AC-23, 400V Rated operation power AC-3, 400V Suitable for ground mounting Suitable for front mounting Suitable for front mounting Suitable for distribution board installation Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC Motor drive optional Voltage release optional		12.1	
Interlockable Motor drive integrated Connection type main current circuit Version as emergency stop installation Type of control element Version as main switch Version as switch disconnector compact Version as maintenance-/service switch Rated operation power at AC-23, 400V Rated operation power at AC-23, 400V Rutable for ground mounting Suitable for front mounting Suitable for front mounting center Suitable for front mounting center Suitable for front mounting center Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC Motor drive optional Voltage release optional	• • •		0
Motor drive integrated Connection type main current circuit Version as emergency stop installation Type of control element Version as main switch Version as switch disconnector compact Version as safety switch Version as safety switch Version as maintenance-/service switch Rated operation power at AC-23, 400V Rated operation power AC-3, 400V Rutol for ground mounting Suitable for front mounting Suitable for front mounting Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC Motor drive optional Version as emergency stop installation Version as maintenance-/service switch No	•		
Connection type main current circuit Version as emergency stop installation Type of control element Version as main switch Version as smin switch Version as switch disconnector compact Version as safety switch Version as maintenance-/service switch Rated operation power at AC-23, 400V Rated operation power AC-3, 400V Rutable for ground mounting Suitable for front mounting Suitable for front mounting Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC Motor drive optional Voltage release optional			
Version as emergency stop installation Type of control element Version as main switch Version as switch disconnector compact Version as safety switch Version as safety switch Version as maintenance-/service switch No Rated operation power at AC-23, 400V Rated operation power AC-3, 400 V Suitable for ground mounting Suitable for front mounting Suitable for front mounting Suitable for front mounting Suitable for front mounting Suitable for intermediate mounting Suitable for intermediate mounting Max. rated operation voltage Ue AC Motor drive optional Voltage release optional	<u> </u>		
Type of control element Version as main switch Version as switch disconnector compact Version as safety switch Version as safety switch Version as maintenance-/service switch Rated operation power at AC-23, 400V Rated operation power AC-3, 400 V Rutable for ground mounting Suitable for front mounting Suitable for front mounting Suitable for front mounting center Suitable for intermediate mounting Mo Suitable for intermediate mounting Max. rated operation voltage Ue AC Motor drive optional Voltage release optional			No
Version as main switch Version as switch disconnector compact Version as safety switch Version as maintenance-/service switch Rated operation power at AC-23, 400V Rated operation power AC-3, 400V Ruitable for ground mounting Suitable for front mounting Suitable for front mounting Suitable for front mounting Suitable for intermediate mounting Suitable for intermediate mounting Max. rated operation voltage Ue AC Motor drive optional Voltage release optional	• , ,		-
Version as switch disconnector compact Version as safety switch Version as maintenance-/service switch Rated operation power at AC-23, 400V Rated operation power AC-3, 400 V Suitable for ground mounting Suitable for front mounting Suitable for front mounting Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC Motor drive optional Voltage release optional	<i></i>		No
Version as safety switch Version as maintenance-/service switch Rated operation power at AC-23, 400V Rated operation power AC-3, 400 V Rated operation power AC-3, 400 V Suitable for ground mounting Suitable for front mounting Suitable for front mounting center Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC Voltage release optional No No No No No No No No No N			
Version as maintenance-/service switch Rated operation power at AC-23, 400V Rated operation power AC-3, 400 V Rated operation power AC-3, 400 V Suitable for ground mounting Suitable for front mounting No Suitable for front mounting center No Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC V O Motor drive optional Voltage release optional	,		
Rated operation power at AC-23, 400V	,		
Rated operation power AC-3, 400 V Suitable for ground mounting Suitable for front mounting Suitable for front mounting center Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC Voltage release optional kWh 0 No No No No No No No No No	·	kWh	
Suitable for ground mounting Suitable for front mounting Suitable for front mounting center Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC Voltage release optional No			
Suitable for front mounting Suitable for front mounting center No Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC Voltage release optional Voltage release optional No			
Suitable for front mounting center Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC Motor drive optional Voltage release optional	•		
Suitable for distribution board installation Suitable for intermediate mounting Max. rated operation voltage Ue AC Voltage release optional No No No No No No No No No N	•		
Suitable for intermediate mounting Max. rated operation voltage Ue AC Voltage release optional No No No No	<u> </u>		
Max. rated operation voltage Ue AC V 0 Motor drive optional No Voltage release optional No			
Motor drive optional No Voltage release optional No	•	V	
Voltage release optional No		·	
	·		
	•		-

Additional product information (links)

Engineering

Linginiouring	
Technical overview ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Ovt_t_p_Leistung_G.pdf	
Key to part numbers, modular system	ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Ovt_t_p_Typenschluessel_G.pdf
Ordering of non-standard switches	ftp://ftp.moeller.net/DOCUMENTATION/PDF/GB/Bestellformulare_de.pdf