


The disconnecting knife in these WK versions swings in and out on a pivot point. The distinctive color of the disconnecting lever signals the open state. The terminals can be connected with the lever open or closed. Designs with a different number and arrangement of test sockets permit reliable measurements using the test plug.

The isolating connector is detachable and can be fitted as a dummy plug. This signals the open state. Designs with different numbers of test sockets permit reliable measurements using the test plug.

Same dimensions as types WK 4 TKG/U and WK 4/TKM/U

WK 4/TKM

fine-stranded solid	V	A
0.5-4 mm ² 0.5-6mm ²	800V/8kV/3*	20
No. 22-10 AWG	600V	20
No. 22-10 AWG	600V*	20
6mm		9mm



WK 4 TKG-TRST/U

fine-stranded solid	V	A
0.5-4 mm ² 0.5-6mm ²	800V/8kV/3*	20
No. 22-10 AWG	300V	10
No. 22-10 AWG	600V*	20
6mm		9mm



WK 4 TKS D/U

fine-stranded solid	V	A
0.5-4 mm ² 0.5-6mm ²	800V/8kV/3	32
No. 22-10 AWG	300V	25
No. 20-10 AWG	600V	20
6mm		9mm



Type	Part No.	Std. Pack	Type	Part No.	Std. Pack	Type	Part No.	Std. Pack
WK 4/TKM/U	57.504.2055.0	100	WK 4 TKG-TRST/U	57.504.4555.0	100	WK 4 TKS D/U	57.504.4455.0	100
WK 4/TKM/U BLAU	57.504.2055.6	100	WK 4 TKG-TRST P3/U	57.504.4855.0	100			
WK 4/TKM/P3/U	57.504.2355.0	100						
35 x 27 x 7,5 EN 60715	98.300.0000.0	1	35 x 27 x 7,5 EN 60715	98.300.0000.0	1	35 x 27 x 7,5 EN 60715	98.300.0000.0	1
35 x 27 x 15 EN 60715	98.370.0000.0	1	35 x 27 x 15 EN 60715	98.370.0000.0	1	35 x 27 x 15 EN 60715	98.370.0000.0	1
9006 EN 60715 G-32	98.190.0000.0	1	9006 EN 60715 G-32	98.190.0000.0	1	9006 EN 60715 G-32	98.190.0000.0	1
WE 1/U	Z5.523.5753.0	100	WE 1/U	Z5.523.5753.0	100	WE 1/U	Z5.523.5653.0	100
9708/2 S 35	Z5.522.8553.0	100	9708/2 S 35	Z5.522.8553.0	100	9708/2 S 35	Z5.522.8553.0	100
WEF 1/35	Z5.523.9353.0	100	WEF 1/35	Z5.523.9353.0	100	WEF 1/35	Z5.523.9353.0	100
AP 4 TK	07.311.6155.0	10	AP 4 TK	07.311.6155.0	10	AP 4 TK	07.311.6155.0	10
AP 4 TK BLAU	07.311.6155.6	10						
TW 4 TK	07.311.8155.0	10	TW 4 TK	07.311.8155.0	10	TW 4 TK	07.311.8155.0	10
IVB 1 WK 4..-2	Z7.255.4227.0	10	IVB 1 WK 4..-2	Z7.255.4227.0	10	IVB 1 WK 4..-2	Z7.255.4227.0	10
IVB 1 WK 4..-3	Z7.255.4327.0	10	IVB 1 WK 4..-3	Z7.255.4327.0	10	IVB 1 WK 4..-3	Z7.255.4327.0	10
IVB 1 WK 4..-6	Z7.255.4627.0	10	IVB 1 WK 4..-6	Z7.255.4627.0	10	IVB 1 WK 4..-6	Z7.255.4627.0	10
* Version with test bolt: CSA: 300V EN 60 947-7-1/DIN VDE 0611 T1 -690V/6kV/3 Test bolt can be loaded with 1A			* Version with test bolt: CSA: 300V EN 60 947-7-1/DIN VDE 0611 T1 -690V/6kV/3 Test bolt can be loaded with 1A					