



## Main

Range of product	Modicon Quantum automation platform
Product or component type	Analogue input module

## Complementary

Analogue input number	8
Input type	Differential
Addressing requirement	9 input words
Analogue input type	Temperature probe - 100...450 °C Pt 100, Pt 200, Pt 500, Pt 1000 Temperature probe - 200...850 °C Pt 100, Pt 200, Pt 500, Pt 1000 Temperature probe - 60...180 °C Ni 100, Ni 200, Ni 500, Ni 1000 Temperature probe 0.5 mA Ni 100, Ni 200, Ni 500, Ni 1000 Temperature probe 2.5 mA Pt 100, Pt 200, Ni 100, Ni 200
Analogue input resolution	13 bits
Input impedance	>= 10 MOhm
Absolute accuracy error	0.1 °C
Linearity error	+/- 0.01 % full scale +/- 0.5 °C
Accuracy drift according to temperature	+/- 0.5 °C at 25 °C +/- 0.9 °C at 0...60 °C
Isolation between channels and bus	2500 V DC for 60 s 1780 V AC 47...63 Hz for 60 s
Isolation between channels	300 Vrms AC
Update time	1200 ms 3 wires 640 ms 2 wires/4 wires
Fault type	Broken wire Overtacking scale
Marking	CE
Local signalling	1 LED green bus communication is present (Active) 1 LED red external fault 8 LEDs green channel is turned on 8 LEDs red channel fault
Bus current requirement	200 mA
Power dissipation in W	1 W
Module format	Standard
Product weight	0.3 kg

## Environment

Standards	CSA C22.2 No 142 UL 508
Product certifications	CUL FM Class 1 Division 2
Resistance to electrostatic discharge	4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Resistance to electromagnetic fields	10 V/m 80...1000 MHz conforming to IEC 801-3
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % without condensation
Operating altitude	<= 5000 m

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0822 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Period	18 months
--------	-----------