

# Sleeve frame - VC-TR3/4M-PEA - 1607075

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Sleeve frame, with PE connection to housing, for contact insert modules, type 3, number of insert modules: 4

The illustration shows the version VC-TR 1/2 M-PEA

## Product Features

- Compact design
- Universal connection
- Proven COMBICON technology
- Can be keyed to prevent incorrect connection

## Key commercial data

<b>package_quantity</b>	5
<b>GTIN</b>	4017918940904

## Technical data

### Dimensions

<b>Height</b>	27.5 mm
<b>Width</b>	80.2 mm

### Ambient conditions

<b>Ambient temperature (operation)</b>	-40 °C ... 100 °C
----------------------------------------	-------------------

### General

<b>Type</b>	VC3
<b>Color</b>	black
<b>Material</b>	PA-GF
<b>Housing material</b>	Plastic
<b>Inflammability class according to UL 94</b>	V0

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	27140816
<b>eCl@ss 4.1</b>	27140816
<b>eCl@ss 5.0</b>	27189239
<b>eCl@ss 5.1</b>	27189239

# Sleeve frame - VC-TR3/4M-PEA - 1607075

## classifications

### eCl@ss

eCl@ss 6.0	27144001
eCl@ss 7.0	27144001
eCl@ss 8.0	27144001

### ETIM

ETIM 2.0	EC000007
ETIM 3.0	EC000007
ETIM 4.0	EC000007
ETIM 5.0	EC000007

### UNSPSC

UNSPSC 6.01	43172601
UNSPSC 7.0901	31261501
UNSPSC 11	43172601
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501


## approvals

---

GOST /

---


### Approval details


-------------------------------------------------------------------------------------

## Drawings

# Sleeve frame - VC-TR3/4M-PEA - 1607075

Functional drawing



Dimensioned drawing

