

## Front adapters - VIP-PA-FLK50/4X14/ 1,0M/S7 - 2322566

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



VIP VARIOFACE front adapter, with connected system cables for SMATIC S7-300, 4 x 8 channels can be connected, cable length: 1 m

### Product Features

- Power supply via terminal blocks with spring-cage double connection
- Can be screwed on with the I/O module
- Encapsulated socket strips on the module side

### Key commercial data

<b>package_quantity</b>	1
<b>GTIN</b>	4046356452304

### Technical data

#### General

<b>Note</b>	Analog I/O cards: To avoid short-circuits, all bridges must be removed! No voltage supply may be supplied to the front adapter!
<b>Note</b>	Digital I/O cards: The front adapter is delivered non-isolated. By removing the bridges, electrical isolation (in groups of 8) can be obtained.
<b>Nominal voltage U<sub>N</sub></b>	< 50 V AC
<b>Nominal voltage U<sub>N</sub></b>	60 V DC
<b>Max. permissible current</b>	1 A (per path)
<b>Channels which can be connected</b>	32
<b>Connection type, connector</b>	IDC/FLK socket strip (2.54 mm)
<b>Number of connectors</b>	4
<b>No. of positions, connector</b>	14
<b>Standards/regulations</b>	IEC 60664
<b>Standards/regulations</b>	IEC 62103
<b>Standards/regulations</b>	DIN EN 50178
<b>Rated surge voltage / insulation</b>	0.8 kV
<b>Pollution degree</b>	2
<b>Surge voltage category</b>	III

#### Ambient conditions

<b>Ambient temperature (operation)</b>	-20 °C ... 50 °C
<b>Ambient temperature (storage/transport)</b>	-20 °C ... 70 °C

## Front adapters - VIP-PA-FLK50/4X14/ 1,0M/S7 - 2322566

### Technical data

#### Supported controller

<b>Controller</b>	SIEMENS S7-300 / ET 200 M
- suitable I/O card	CPU 313C
- suitable I/O card	CPU 313C-2PtP
- suitable I/O card	CPU 313C-2DP
- suitable I/O card	CPU 314C-2PtP
- suitable I/O card	CPU 314C-2DP
- suitable I/O card	6ES7 321-1BL00-0AA0
- suitable I/O card	6ES7 322-1BL00-0AA0
- suitable I/O card	6ES7 322-8BH01-0AB0
- suitable I/O card	6ES7 323-1BL00-0AA0
- suitable I/O card	6ES7 331-7NF00-0AB0
- suitable I/O card	6ES7 331-7NF10-0AB0
- suitable I/O card	6ES7 331-7PF01-0AB0
- suitable I/O card	6ES7 331-7PF11-0AB0
- suitable I/O card	6ES7 350-2AH01-0AE0
- suitable I/O card	6ES7 357-4AH01-0AE0

### classifications

#### eCl@ss

eCl@ss 4.0	27060306
eCl@ss 4.1	27060306
eCl@ss 5.0	27061801
eCl@ss 5.1	27061801
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801
eCl@ss 8.0	27061801

#### ETIM

ETIM 2.0	EC000237
ETIM 3.0	EC000237
ETIM 4.0	EC000237
ETIM 5.0	EC002584

#### UNSPSC



UNSPSC 6.01	26121620
UNSPSC 7.0901	26121620
UNSPSC 11	26121620
UNSPSC 12.01	26121620
UNSPSC 13.2	26121620

# Front adapters - VIP-PA-FLK50/4X14/ 1,0M/S7 - 2322566

approvals

UL Recognized / cUL Recognized / cULus Recognized /

Approval details



Drawings

Circuit diagram

