

# Power supply unit - MINI-PS-100-240AC/ 5DC/3 - 2938714

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



DIN rail power supply unit 5 V DC/3 A, primary-switched mode, slim design

## Product Features

- Easy-maintenance connection technology thanks to keyed COMBICON connectors
- Remote monitoring of output voltage via switching output



## Key commercial data

package_quantity	1
GTIN	4017918900502

## Technical data

### Dimensions

Width	22.5 mm
Height	99 mm
Depth	107 mm

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 70 °C (> 60 °C derating)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	≤ 95 % (at 25 °C, non-condensing)
Noise immunity	EN 61000-6-2:2005

### Input data

Input voltage range	85 V AC ... 264 V AC
Input voltage range	90 V DC ... 350 V DC
AC frequency range	45 Hz ... 65 Hz
Current consumption	0.4 A (120 V AC)
Current consumption	0.2 A (230 V AC)
Current consumption	0.4 A (90 V DC)
Current consumption	0.2 A (350 V DC)
Inrush surge current	< 15 A (typical)
Power failure bypass	> 30 ms (120 V AC)

# Power supply unit - MINI-PS-100-240AC/ 5DC/3 - 2938714

## Technical data

### Input data

<b>Power failure bypass</b>	> 140 ms (230 V AC)
<b>Input fuse</b>	2 A (slow-blow, internal)
<b>Choice of suitable fuses</b>	6 A ... 16 A (Characteristics B, C, D, K)

### Output data

<b>Nominal output voltage</b>	5 V DC $\pm$ 1%
<b>Setting range of the output voltage</b>	4.5 V DC ... 5.5 V DC (> 5 V constant capacity)
<b>Output current</b>	3 A (-25 °C ... 60 °C)
<b>Output current</b>	5 A (with POWER BOOST, -25°C ... 40°C permanent)
<b>Derating</b>	60 °C ... 70 °C (2.5%/K)
<b>Connection in parallel</b>	Yes, for assembling redundant systems and increasing efficiency
<b>Connection in series</b>	Yes
<b>Residual ripple</b>	< 40 mV <sub>PP</sub> (20 MHz)
<b>Peak switching voltages nominal load</b>	< 100 mV <sub>PP</sub> (20 MHz)
<b>Maximum power dissipation NO-Load</b>	1 W
<b>Power loss nominal load max.</b>	5 W

### General

<b>Net weight</b>	0.17 kg
<b>Operating voltage display</b>	Green LED
<b>Efficiency</b>	> 73 % (for 230 V AC and nominal values)
<b>Insulation voltage input/output</b>	4 kV (type test)
<b>Insulation voltage input/output</b>	3 kV (Routine test)
<b>Protection class</b>	II (in closed control cabinet)
<b>MTBF (IEC 61709, SN 29500)</b>	> 500000 h (According to EN 29500)
<b>Mounting position</b>	horizontal DIN rail NS 35, EN 60715
<b>Assembly instructions</b>	Can be aligned: Horizontally 0 mm, vertically 50 mm
<b>Electromagnetic compatibility</b>	Conformance with EMC Directive 2004/108/EC
<b>Noise emission</b>	EN 50081-2
<b>Low Voltage Directive</b>	Conformance with LV directive 2006/95/EC
<b>Standard – Electrical equipment of machines</b>	EN 60204
<b>Standard - Electrical safety</b>	EN 60950-1/VDE 0805 (SELV)
<b>Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations</b>	EN 50178/VDE 0160 (PELV)
<b>Standard – Safety extra-low voltage</b>	EN 60950-1 (SELV)
<b>Standard – Safety extra-low voltage</b>	EN 60204 (PELV)
<b>Standard - Safe isolation</b>	DIN VDE 0100-410
<b>Standard – Protection against electric shock</b>	DIN 57100-410
<b>Standard – Limitation of mains harmonic currents</b>	EN 61000-3-2
<b>UL approvals</b>	UL/C-UL listed UL 508
<b>UL approvals</b>	UL/C-UL Recognized UL 60950

# Power supply unit - MINI-PS-100-240AC/ 5DC/3 - 2938714

## Technical data

### General

<b>UL approvals</b>	UL ANSI/ISA-12.12.01 Class I, Division 2, Groups A, B, C, D (Hazardous Location)
<b>Surge voltage category</b>	III

### Connection data, input

<b>Connection method</b>	Pluggable screw connection
<b>Conductor cross section solid min.</b>	0.2 mm <sup>2</sup>
<b>Conductor cross section solid max.</b>	2.5 mm <sup>2</sup>
<b>Conductor cross section stranded min.</b>	0.2 mm <sup>2</sup>
<b>Conductor cross section stranded max.</b>	2.5 mm <sup>2</sup>
<b>Conductor cross section AWG/kcmil min.</b>	24
<b>Conductor cross section AWG/kcmil max</b>	12
<b>Stripping length</b>	7 mm
<b>Screw thread</b>	M3

### Connection data, output

<b>Connection method</b>	Pluggable screw connection
<b>Conductor cross section solid min.</b>	0.2 mm <sup>2</sup>
<b>Conductor cross section solid max.</b>	2.5 mm <sup>2</sup>
<b>Conductor cross section stranded min.</b>	0.2 mm <sup>2</sup>
<b>Conductor cross section stranded max.</b>	2.5 mm <sup>2</sup>
<b>Conductor cross section AWG/kcmil min.</b>	24
<b>Conductor cross section AWG/kcmil max</b>	12
<b>Stripping length</b>	7 mm

### Signaling

<b>Output name</b>	DC OK active
<b>Status display</b>	"DC OK" LED green
<b>Conductor cross section solid min.</b>	0.2 mm <sup>2</sup>
<b>Conductor cross section solid max.</b>	2.5 mm <sup>2</sup>
<b>Conductor cross section stranded min.</b>	0.2 mm <sup>2</sup>
<b>Conductor cross section stranded max.</b>	2.5 mm <sup>2</sup>
<b>Conductor cross section AWG/kcmil min.</b>	24
<b>Conductor cross section AWG/kcmil max</b>	12
<b>Screw thread</b>	M3

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	27040702
<b>eCl@ss 4.1</b>	27040702
<b>eCl@ss 5.0</b>	27049002
<b>eCl@ss 5.1</b>	27049002
<b>eCl@ss 6.0</b>	27049002

# Power supply unit - MINI-PS-100-240AC/ 5DC/3 - 2938714

## classifications

### eCl@ss

eCl@ss 7.0	27049002
eCl@ss 8.0	27049002

### ETIM

ETIM 2.0	EC001039
ETIM 3.0	EC001039
ETIM 4.0	EC000599
ETIM 5.0	EC002540

### UNSPSC

UNSPSC 6.01	30211502
UNSPSC 7.0901	39121004
UNSPSC 11	39121004
UNSPSC 12.01	39121004
UNSPSC 13.2	39121004

## approvals

UL Listed / cUL Listed / cULus Listed / UL Recognized / UL Listed / cUL Recognized / GOST / cUL Listed / cULus Recognized / cULus Listed /

### Approval details

UL Listed



cUL Listed

cULus Listed

UL Recognized

# Power supply unit - MINI-PS-100-240AC/ 5DC/3 - 2938714

approvals



## Drawings

Block diagram

