

Thermocouple measuring transducer - MCR-TE-J-K-I-NC - 2810586

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Temperature transducers for thermocouples type J, K, configurable via DIP switch, input: 0...400 °C, 0...800 °C, 0...1000 °C, 0...1200 °C, output signal 0(4)...20 mA

The illustration shows version MCR-TE-JK-U-E



Key commercial data

package_quantity	1
GTIN	4017918275235

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

classifications

eCl@ss

eCl@ss 4.0	27200206
eCl@ss 4.1	27200206
eCl@ss 5.0	27200206
eCl@ss 5.1	27200206
eCl@ss 6.0	27200206
eCl@ss 7.0	27200206
eCl@ss 8.0	27200206

ETIM

ETIM 2.0	EC001446
ETIM 3.0	EC001446
ETIM 4.0	EC001446
ETIM 5.0	EC001446

UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	39121008

Thermocouple measuring transducer - MCR-TE-J-K-I-NC - 2810586

classifications



UNSPSC

UNSPSC 11	39121008
UNSPSC 12.01	39121008
UNSPSC 13.2	39121008

approvals

UL Recognized / cUL Recognized / cULus Recognized /

Approval details



Drawings

© Phoenix Contact 2014 - all rights reserved
<http://www.phoenixcontact.com>