

## Power storage devices - QUINT-BAT/24DC/ 3.4AH - 2866349

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Power storage device, lead AGM, VRLA technology, 24 V DC, 3.4 Ah. Connection via pin cable lug, 14 mm.

### Key commercial data

<b>package_quantity</b>	1
<b>GTIN</b>	4017918959746

### Technical data

#### Ambient conditions

<b>Degree of protection</b>	IP20
<b>Ambient temperature (operation)</b>	0 °C ... 40 °C

#### Input data

<b>Nominal input voltage</b>	24 V DC
------------------------------	---------

#### Output data

<b>Nominal output voltage</b>	24 V DC
<b>Output current</b>	max. 25 A
<b>Connection in parallel</b>	Yes, for increasing the buffer period
<b>Connection in series</b>	No
<b>Output fuse</b>	25 A

#### General

<b>IQ technology</b>	No
<b>Memory medium</b>	battery 3.4 Ah
<b>Shipbuilding approval</b>	Germanischer Lloyd (EMC 2), ABS

### classifications

#### ETIM

<b>ETIM 4.0</b>	EC000357
<b>ETIM 5.0</b>	EC000357

### approvals

## Power storage devices - QUINT-BAT/24DC/ 3.4AH - 2866349

approvals

---

Approval details

GL

BSH

accessories

**Assembly adapter**

QUINT-ADAPTER/4 - 2866857



**Fuse**

---

SI FORM C 25 A DIN 72581 - 0913757



**Drawings**

© Phoenix Contact 2014 - all rights reserved  
<http://www.phoenixcontact.com>