

## Power storage devices - QUINT-BAT/24DC/ 7.2AH - 2866352

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Power storage device, lead AGM, VRLA technology, 24 V DC, 7.2 Ah. Connection via pin cable lug, 14 mm.



### Key commercial data

<b>package_quantity</b>	1
<b>GTIN</b>	4017918959753

### Technical data

#### Dimensions

<b>Width</b>	164 mm
<b>Height</b>	156 mm
<b>Depth</b>	110 mm

#### Ambient conditions

<b>Degree of protection</b>	IP20
<b>Ambient temperature (operation)</b>	0 °C ... 40 °C
<b>Ambient temperature (storage/transport)</b>	0 °C ... 40 °C

#### Input data

<b>Nominal input voltage</b>	24 V DC
------------------------------	---------

#### Output data

<b>Nominal output voltage</b>	24 V DC
<b>Output current</b>	max. 50 A
<b>Connection in parallel</b>	Yes, for increasing the buffer period
<b>Connection in series</b>	No
<b>Output fuse</b>	2x 25 A

#### General

<b>IQ technology</b>	No
<b>Net weight</b>	6 kg
<b>Memory medium</b>	battery 7.2 Ah
<b>Protection class</b>	III
<b>Shipbuilding approval</b>	Germanischer Lloyd (EMC 2), ABS

# Power storage devices - QUINT-BAT/24DC/ 7.2AH - 2866352

## Technical data

### classifications

#### eCl@ss

eCl@ss 4.0	27040603
eCl@ss 4.1	27040603
eCl@ss 5.0	27040603
eCl@ss 5.1	27040603
eCl@ss 6.0	27040603
eCl@ss 7.0	27040603
eCl@ss 8.0	27040603

#### ETIM

ETIM 2.0	EC000382
ETIM 3.0	EC000382
ETIM 4.0	EC000357
ETIM 5.0	EC000357

#### UNSPSC

UNSPSC 6.01	30211510
UNSPSC 7.0901	39121011
UNSPSC 11	39121011
UNSPSC 12.01	39121011
UNSPSC 13.2	39121011

### approvals

GL /

#### Approval details

GL
----

### accessories

#### Assembly adapter

QUINT-ADAPTER/4 - 2866857



# Power storage devices - QUINT-BAT/24DC/ 7.2AH - 2866352

accessories

## Fuse

SI FORM C 25 A DIN 72581 - 0913757



---

## Drawings

Block diagram

